

## Wood burning heater Harvia Pro 20 Duo Steel

WKPR20DUOS

*Harvia Pro 20 DUO - the fire behind the glass hatch of this wood-burning heater creates the atmosphere of the fireplace to the room next to the sauna and allows you to heat the sauna from outside. Harvia Pro 20 DUO is the source of strong steam in medium-sized saunas. The heater's stone capacity ensures enjoyable sauna baths and a hot sauna room in a short time. The model is equipped with adjustable feet for easy installation, which makes it easy to adjust the height of the chimney opening to the right position. The heater can be equipped with a separate chimney model water tank. The outer shell of the heater is made of stainless steel. Harvia DUO heaters allows more freedom when deciding sauna bench solutions. Water heating can b*



### Advantages

- Harvia Pro 20 DUO woodburning heater with a large glass hatch for medium-sized saunas with a wall embedded glass hatch
- The stone capacity ensures a quickly heating and hot sauna
- Adding firewood from outside the sauna is easy and keeps the sauna room clean
- Convenient removal of ashes from outside the sauna
- Pipe connection (115 mm) on top of the stove

### Features

Main material : Steel

H x W x D : 760.0 x 430.0 x 790.0 mm

Net weight (kg) : 80.0

Stone amount (kg) : 40.0

| ID         | GTIN          | Power   | Sauna room size min - max m3 |
|------------|---------------|---------|------------------------------|
| WKPR20DUOS | 6417659036580 | 24.1 kW | 8.0-20.0                     |

## Spare parts

| Product                                    | ID           | Pcs |
|--|--------------|-----|
| Stainless steel frame for Duo-stoves       | WX044        |     |
| Casing, stainless steel, 20 Duo            | WX045        |     |
| Furnace grate                              | ZKIP-10      |     |
| Connection pipe                            | ZKIP-130     |     |
| Stove body 20 SL Duo                       | ZROST-300LUX |     |
| Adjustable legs for LG150/SL               | SPZKIP-918   |     |
| Hinge pin                                  | SPZKIP-50    |     |
| Stainless steel frame for Duo-stoves       | SP044        | 1   |
| Handle for Duo stoves door                 | SP095        | 1   |
| Air flow spoiler Pro 2019                  | SPZROST-601  |     |
| Cap for smoke hole (Ø 50 mm)               | SPZKIP-170   | 1   |
| Ash box, Duo-series                        | SP096        | 1   |
| Door with glass for Duo                    | SP098        | 1   |
| Connection pipe 200 mm                     | SPZKIP-130   | 1   |
| Glass 4x236x360 mm Festia/Duo, transparent | SPZTS-45     | 1   |
| Cast-iron grating 135x290mm, sauna heaters | SPZKIP-10    | 1   |

## Technical details

| Technical data                            | Type / attribute   | WKPR20DUOS |
|---|--|------------|
|   | Color  | Black      |
|   | Power output   | 24.1 kW    |
|   | Stone sizes  | Ø10-15 cm  |
|   | Stone amount (kg)  | 40         |
| <b>Dimensions</b>                         | Product width  | 430        |
|   | Product height   | 760        |
|   | Product depth (mm)   | 790        |
|   | Net weight (kg)  | 80         |
| <b>Connections</b>                        | Flue connection locations  | Top        |
|   | Chimney connection diameter  | 115        |
| <b>Safety and installation dimensions</b> | Safety distance front (non-combustible materials)                              | 300        |
|   | Safety distance front (combustible materials)                                  | 300        |
|   | Safety distance right side (combustible materials)                             | 300        |
|   | Safety distance right side non-combustible materials                           | 100        |
|   | Safety distance left side (combustible materials)                              | 300        |
|   | Safety distance left side non-combustible materials                            | 100        |
|   | Safety distance behind (non-combustible materials)                             | 100        |
|   | Safety distance behind (combustible materials)                                 | 300        |
|   | Safety distance (Ceiling)  | 1300       |
|   | Room min. height(depends on connections and therefore from output, star/delta) | 2060       |